






GRABOPLAST

Ballerina

Technical parameter	Standard	Unit	Result
Construction			heterogeneous
Total thickness	EN ISO 24346	mm	1.4
Wear layer thickness	EN ISO 24340	mm	0.5
Length of rolls	EN ISO 24341	m	20
Width of rolls	EN ISO 24341	m	2
Total weight	EN ISO 23997	kg/m ²	2
Residual indentation	EN ISO 24343	max. mm	0.1
Dimensional stability	EN ISO 23999	max.%	±0.2
Curling	EN ISO 23999	max.mm	8
Reaction to fire	EN 13501-1	class	B _{fl} -s1
Abrasion group	EN 660-2	group	T
Light fastness	EN ISO 105-B02	grade	> 6
Chemical resistance	EN ISO 26987	-	high resistance
Slip resistance	EN 13893	class	DS
Castor chair resistance	ISO 4918 / EN 425		slight change
Flexibility (diameter 20/40mm)	EN ISO 24344	visual evaluation	no damage
Surface treatment			CLP
Antibacterial and fungicid treatment			graboSAN
Environmental attributes			Solvent and heavy metal free product
CE MARKING	EN 14041		✓

GRABOPLAST Floor Covering Manufacturers Ltd.
H-9023 Győr, Fehérvári út 16/b tel.: (36) 96 506 100
mail@graboplast.hu www.graboplast.hu