

PROTECTSPORT T

Technical datasheet

Technical parameter	Standard	Unit	Result
DESCRIPTION			
Construction			protecting covering
Thickness	EN ISO 24346	mm	1,0
Width of roll	EN ISO 24341	cm	200
Length of roll	EN ISO 24341	lm	35
Hardness Shore A	ISO 868		95
Weight	EN ISO 23997	kg/m ²	1,2
CLASSIFICATION			
Dimensional stability	EN ISO 23999	max. %	0,2
Residual indentation	EN ISO 24343	max. mm	0,05
PERFORMANCE			
Fire resistance	EN 13501-1	class	Bfl-s1
Tensile strength	ISO 1421B	N/5cm	550/550
Elongation at break	ISO 1421B	%	210/210
Tear strength	ISO 4674A2	N	40/40
Abrasion resistance	ISO 9352	TaberH18 1000C max. mg	100
Light fastness	ISO 105-B02	48 hours	min.6
Content of PCP	EN 12673		does not contain
Formaldehyde emission	ENV 717-1		E1 (no emission)
Warranty	At least for min 5 times/year	year	1
	Less then 5 times/year	year	2
GRABOPLAST Floor Covering Manufacturers Ltd. H-9023 Győr, Fehérvári út 16/b tel.: (36) 96 506 100 mail@graboplast.hu www.graboplast.hu			