




## SpringAir Elite

Area elastic sport parquet system			
Property	Standard	Unit	Result
<b>DESCRIPTION</b>			
SpringAir sport parquet top layer	Multi layered wooden parquet according to EN 13489; With 5,2 mm hardwood wear layer		
Underlay system	Shock Pad boarded shockabsorbing foam		
Thickness	EN 13647	mm	46 ± 0,5
Weight	-	kg/m <sup>2</sup>	14
<b>CLASSIFICATION</b>			
Product specification	Indoor sport parquet system for professional multisport applications. Category A3 according to EN 14904.		
Thermal resistance	EN 12664	m <sup>2</sup> K/W	0,38
Reaction to fire	EN 13501	-	Cfl-s1
Formaldehyde content	EN 717-2	-	E1
Pentachlorophenol	-	-	No pentachlorophenol
<b>SPORT PROPERTIES</b>			
Friction	EN 13036-4	-	80-110
Shock absorption	EN 14808	%	53
Vertical deformation	EN 14809	mm	2,5
Ball rebound	EN 12235	%	97
Specular gloss	EN 2813	%	< 30
<b>TECHNICAL CHARACTERISTICS</b>			
Resistance to rolling load	EN 1569	N	<1500
Chemical resistance	EN 13442	-	no change
Abrasion resistance (CS10 wheel)	EN ISO 5470-1	mg/1000cycles	< 80
<b>OTHERS</b>			
Limited warranty		5 years	
Dimensions	SpringAir sportparquet	2250 x 190 x 18 mm	
	ShockPad Elite	2550 x 1125 x 27mm	

**GRABOPLAST Floor Covering Manufacturers Ltd.**

H-9023 Győr, Fehérvári út 16/b tel.: (36) 96 506 100

mail@graboplast.hu www.graboplast.hu