

iD Click Ultimate 55-70

Datasheet

	Norm	iD Click Ultimate 55	iD Click Ultimate 70
Classification			
Product type	EN ISO 10582	Heterogeneous poly(vinyl chloride) floor coverings	
Domestic classification	EN ISO 10874	23 Heavy	
Commercial classification	EN ISO 10874	33 Heavy	34 Very Heavy
Technical Characteristics			
Total thickness	EN ISO 24346	6,50 mm	
Wear layer thickness	EN ISO 24340	0,55 mm	0,70 mm
Total weight	EN ISO 23997	10700 g/m ²	10600 g/m ²
Binder content	EN ISO 10582	Type I	
Surface treatment		TEKTANIUM®	
Embossing in Register		Yes	
Bevelled edges		4 sides	
Installation method		Click	
Performance for CE Marking			
Declaration of Performance #	EN 14041	0197-0057-DoP-2022-11	0197-0058-DoP-2022-11
Technical Performance			
Dimensional stability	EN ISO 23999	Average measured value : ≤ 0.10 % ≤ 0,15 %	
Curl resultant to heat	EN ISO 23999	≤ 1 mm	
Reaction to fire	EN 13501-1	Bfl-s1	
Residual indentation	EN ISO 24343-1	Average measured value: 0,02 mm Required value: ≤ 0,10 mm	
Castor chair	EN ISO 4918	No damage	
Impact sound reduction - ΔLw	EN ISO 717-2	19 dB	
Reduction of in-room impact noise	NF S31-074	Class C (≤ 85 dB)	
Thermal resistance	EN ISO 10456	0,07 m ² •K/W	
Colour fastness to light	EN ISO 105-B02	≥ 6	
Chemical resistance	EN ISO 26987	Good resistance	
Slip resistance	DIN 51130	R10	
Slip resistance	EN 13893	Class DS (μ ≥ 0,30)	
Peeling Resistance	EN ISO 24345	≥ 50N/50mm	
Underfloor heating		Suitable (subfloor temperature maximum 27°C)	
Sustainability performances			
Recyclability through ReStart®		Recyclable	
Recycled content	ISO 14021	20 %	
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		12,26 kg CO ₂ eq /m ²	
Total Carbon Footprint (EPD Modules A-D, incl. recycling scenario)		6,41 kg CO ₂ eq /m ²	
Total VOC Emissions	EN 16516	Platinum (≤ 10 μg/m ³)	
Dimensions and designs			
Plank		Plank 1200 x 200,5mm - 5 planks=1,203 m ² /box - 60 boxes/pallet Plank 1200 x 306mm - 3 planks=1,102 m ² /box - 66 boxes/pallet Plank 1500 x 243mm - 3 planks=1,094 m ² /box - 66 boxes/pallet	Plank 1200 x 200,5mm - 5 planks=1,203 m ² /box - 60 boxes/pallet Plank 1200 x 306mm - 3 planks=1,102 m ² /box - 69 boxes/pallet Plank 1500 x 243mm - 3 planks=1,094 m ² /box - 69 boxes/pallet
Tile		Tile 640 x 320mm - 7 tiles=1,434 m ² /box - 52 boxes/pallet Tile 960 x 480mm - 3 tiles=1,382 m ² /box - 54 boxes/pallet	
Number of designs available		43	43

Slip resistance DIN : R9/R10 depending on embossing
Embossing in Register : on Authentics references



The above information is subject to modification for the benefit of further improvement (03/10/2023). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com>. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.